Analysis of furan and alkylfurans in food commodities using headspace SPME arrow and GC-MS

Introduction

- Furan and alkylfurans are produced during heating of foodstuff as a result of the thermal degradation of compounds such as carbohydrates, ascorbic acid, and derivatives, as well as some lipids.
- The International Agency for Research of Cancer classified furan as a possible carcinogenic compound, and there is a general concern on the possible health risks associated with the occurrence of furans and alkylfurans in food.
- Methods reported for the analysis of these volatile organic compounds include static headspace (HS) and solid phase microextraction (SPME) in combination with GC-MS.
- The use of SPME for the analysis of these highly volatile analytes has demonstrated improved method sensitivity and higher S/N for some of the alkylfurans. However, the fragility of traditional SPME fibers can be a concern.
- In this work, we present a HS-SPME-GC-MS method for the analysis of furans and alkylfurans in baby formula and coffee using a SPME arrow.

Goal

To develop a workflow using the SPME arrow coupled to GC-MS for the analysis of furan and alkylfurans in baby formula and coffee

Methods **Instrumental Analysis**

Table 1. GC-MS conditions for the analysis of furan and alkylfurans.

Instrument	Agilent 7890B GC & 5977B MSD
Column	Rxi-624Sil MS, 30 m, 0.25 mm ID, 1.40 µm
Column	(Restek cat.# 13868)
Injection Mode	Split (1:10 and 1:100)
Liner	Topaz 1.8 mm ID SPME/straight liner
	(cat# 23280)
Inj. Temp.	280°C
Split Flow	14.0 mL/min (10:1) and 140 mL/min (100:1)
Purge Flow	5 mL/min
Oven	35°C (hold 3 min) to 75°C by 8°C/min, then to
Oven	200°C (hold 1 min) by 25°C/min
Carrier Gas	He, constant flow
Flow Rate	1.40 mL/min
Analyzer	MS (quadrupole)
Acquisition Type	SIM
Ionization Mode	EI (70 eV)
Transfer Line Temp.	280 °C
Source Temp.	325 °C
Quadrupole Temp.	200 °C
Solvent delay	2.2 min




Figure 1. GC-MS chromatogram corresponding to furan and alkyl furan standards and internal standards.

Nathaly Reyes-Garcés; Joe Konschnik

Restek Corporation, Bellefonte, PA, USA

Table 2. MS parameters for the analysis of furan, alkylfurans, and their internal standards (SIM mode).

Segment start time, min	Compound (Rt, min)	lons	Dwell time, ms		
	$E_{\rm urop} \left(2.447 \right)$	39			
2.2	Furan (2.447)	68*	50		
2.2	$F_{\rm urop} d4 (0.400)$	42	50		
	Furan-d4 (2.428)	72*			
		53			
	2-Methylfuran (4.536)	81	30		
		82*			
4 2		53			
4.2	3-Methylfuran (4.846)	81	30		
		82*			
	2 Mothylfuron d6 (1 161)	58	20		
	2-Methylfuran-d6 (4.464)	88*	30		
		53			
	2-Ethylfuran (7.100)	81*	30		
		96			
	2-Ethylfuran-d5 (7.001)	55	30		
6.6	2-Eurynuran-u5 (7.001)	101*	30		
	2,5-Dimethylfuran (7.243)	67	30		
	2,5-Dimetryilulari (7.243)	95*			
	2,5-Dimethylfuran-d3 (7.179)	84	30		
		99*			
	2-Pentylfuran (11.570)	81	30		
10.6		138*	30		
0.01	2-Pentylfuran-d11 (11.501)	83	30		
		149*	30		

*Quantifier ions

Sample Preparation





Figure 2. Sample preparation workflow.

Table 3. Sample preparation conditions for baby formula and coffee samples.

Sample	Baby formula	Coffee			
Amount	0.5	5 g			
Volume of 30% NaCl solution added	10 mL	5 mL			
Volume of internal standard solution added	50 μL (1 μg/mL solution)	40 μL (25 μg/mL solution)			
Incubation time	10	min			
Incubation and extraction temperature	50°C				
Agitation	250 rpm				
HS-SPME extraction time	10 min	1 min			
Desorption temperature	280)°C			
Desorption time	1 min				



Calibration

• Calibration curves were constructed for all the target analytes in sodium chloride solution (30%) using appropriate deuterated analogues for each of them.

• Two calibration curves were prepared in 30% sodium chloride solution one for the analysis of low concentrations of furans in baby formula (1.25 – 150 ng in vial), and one for the quantitation of high concentrations target analytes in coffee (25 – 8000 ng in vial).

• Internal standard solutions were added to each calibration vial (50 μ L of the 1 μ g/mL solution for the low concentration calibration curve, and 40 µL of the 25 µg/mL solution for the high concentration calibration curve).

• Calibration curves were then constructed by plotting analyte area/ISTD average area ratios (n=2) versus spiked concentration.




Figure 5. Responses of all analytes obtained with three sample prep techniques (n=3). CWR: Carbon Wide Range. • For the SPME devices, we selected a CWR coating because it is the best phase for the extraction of highly volatile compounds of low molecular weight.

As seen in Figure 5, the SPME-based techniques significantly outperformed HS analysis, and the SPME Arrow provided the best results in terms of analyte responses in all the cases.

SPME Arrow: Experimental Conditions Desorption: Based on a carryover evaluation, desorption temperature and time of 280°C and 1 min, respectively, were selected. **Extraction temperature:** The effect of three extraction temperatures (40, 50 and 60°C) was evaluated on the responses of analytes spiked in baby formula. Results demonstrated a decrease in the response of the most volatile analytes with an increase of the extraction temperature. 2ethylfuran and 2,5-dimethylfuran did not show a significant difference in the responses obtained at 40 and 50°C, whereas 2-pentylfuran exhibited a slight increase in the response with an increase in the extraction temperature. We considered 50°C to be a good compromise for all the analytes. 10 min was selected as incubation time. Extraction time: Extraction time profiles were constructed for all target analytes. Extractions were carried out from the headspace of vials containing baby formula and sodium chloride solution spiked with all the analytes at 40 µg/kg. Extractions were conducted for 1, 2, 5, 10 and 20 min. As shown in Figure 6, the most volatile analytes (e.g. furan) reached equilibrium at 10 min, whereas the rest of the compounds did not reach a plateau at the evaluated extractions times. As a compromise, 10 min was chosen as the extraction

Coffee analysis: To enable the analysis of coffee with the SPME arrows, the GC split was set to 1:100; the extraction time was set to 1 min; and the volume of sodium chloride solution

A HS-SPME-GC-MS method was developed for the analysis of furans and alkyl furans in baby formula and coffee. Different experimental conditions were evaluated and optimized. Satisfactory results in terms of linearity, accuracy and precision were obtained in the majority of the cases. Accuracy values above 111% in coffee samples spiked at 4000 µg/kg could be due to sample handling, but additional experimental work may be needed to further understand this bias.

 Pawliszyn, J., Handbook of Solid Phase Microextraction. Chemical Industry Press, Beijing 2009. • Frank, N., Dubois, M., Huertas Pérez, J. F., Detection of Furan and five Alkylfurans, including 2-Pentylfuran, in various Food Matrices. J. Chromatogr. A 2020, 1622, 461119.

le 4. Analy) and inst				lfu	ra	ns i	in	ba	by	foi	rm	ula	Ì
					/	•						•	1

Analyte	Blan	k (n=3)		nc.(n=3), /kg*	High conc. (n=3), 50 μg/kg*			
	µg/kg	RSD, %	Acc., %	RSD, %	Acc., %	RSD, %		
n	16	1	110	2	94	4		
ethylfuran	60	2	97	2	100	3		
ethylfuran	-	-	- 113 3		107	6		
nylfuran	67	2	93	3	105	5		
Dimethylfuran	-	-	101	4	97	14		
ntylfuran	219	3	87	11	108	12		
Analyte	Blan	k (n=3)		nc.(n=3), ug/kg*		nc. (n=3), µg/kg*		
Analyte	Blan µg/kg	k (n=3) RSD, %		ug/kg*		µg/kg*		
Analyte n		. ,	1000 µ	ug/kg*	4000	µg/kg*		
	µg/kg	RSD, %	1000 µ Acc., %	Ig/kg* RSD, %	4000 Acc., %	µg/kg* RSD, %		
n	µg/kg 394	RSD, % 10	1000 µ Acc., % 87	Ig/kg* RSD, % 2	4000 Acc., % 125	µg/kg* RSD, % 3		
n ethylfuran	µg/kg 394 843	RSD, % 10 10	1000 p Acc., % 87 94	Jg/kg* RSD, % 2 3	4000 Acc., % 125 116	µg/kg* RSD, % 3 2		
n ethylfuran ethylfuran	µg/kg 394 843 96	RSD, % 10 10 10	1000 Acc., % 87 94 87	Jg/kg* RSD, % 2 3 2	4000 Acc., % 125 116 119	µg/kg* RSD, % 3 2 3		
n ethylfuran ethylfuran nylfuran	µg/kg 394 843 96 29	RSD, % 10 10 10 10 11	1000 Acc., % 87 94 87 93	Jg/kg* RSD, % 2 3 2 2 2 2	4000 Acc., % 125 116 119 115	µg/kg* RSD, % 3 2 3 5		